

Telehandler / Zoom Boom

Used Telehandler Santa Clarita - Telehandlers go by many different names including a boom lift, telescopic handler, Cherry picker or teleporter. This industrial equipment is commonly used in a variety of industries including agriculture. It is similar to a forklift and a crane as it has a boom, enabling it to extend upwards and forwards from the vehicle. Numerous attachments can be placed at the end of the articulating boom to conduct a variety of different jobs. Different attachments such as a bucket, pallet forks, a muck grab or a winch can help the machine complete many jobs. The pallet forks are the most popular telehandler attachment. Pallet forks enable the operator to move loads to and from a variety of locations that would otherwise be considered unreachable with a standard forklift. These machines enable cargo pallets to be unloaded and loaded from a trailer and placed on rooftops, racking or other high and hard to access locations. Often, high rooftop locations would need a crane although, telehandlers can accomplish these tasks much more efficiently. Of course, it isn't always affordable or practical to use secondary equipment or a crane to complete certain tasks. A bucket grab or a bucket is the most common attachments for telehandlers within the agricultural sector. Relocating items from hard to reach areas that cannot rely on a wheeled loader or a backhoe loader give telehandlers a significant advantage. For instance, these industrial machines can directly access a hopper or trailer with high sides; applications that would otherwise rely on a conveyor, loading ramp or similar equipment. Relying on one piece of equipment to complete a variety of jobs saves time, money and storage. Telehandler machines can work in conjunction with a crane jib. Numerous attachments can be utilized including power booms, grain buckets, dirt buckets and rotators. Three-point linkage and power take-off can be used with agricultural models to make this machine particularly capable. Interestingly enough, the machines' main advantage is also its' biggest limitation. The boom raises or extends with heavy loads, acting as a lever. Even with rear counterweights, this machine may become unstable from time to time; decreasing the lift capacity when the distance between the center of the load and the front of the wheels or the working radius increases. If the machine works as a single boom loader instead of using twin arms while carrying a large load, there is a chance that weakness can occur even in the most carefully designed units. For instance, a telehandler with a five thousand pound capacity may be capable of safely lifting as little as four hundred pounds fully extended with a low boom angle with a retracted boom. The same piece of equipment with a five thousand pound lift capacity and retracted boom may be capable as supporting up to ten thousand pounds once the boom is raised to seventy degrees. Monitoring the angle, weight and boom height, there are load charts on this equipment to outline which tasks can be safely conducted. Updated telehandler models have computers and sensors. The operator cannot continue once the machine's limits have been reached. They are warned and cut off from accessing the control input. The lifting capacity is enhanced by front stabilizers that maximize the lifting capacity from a stationary position. A mobile crane can also use a bucket is another option consisting of a stabilized rotary joint found between upper and lower frames. There are compact telehandler models that differ in boom design, size, reach and weight. Telehandlers that weigh 11,000 pounds or less fall into the compact category. A two-stage boom is a popular option for compact models whereas the three or four boom design is common for bigger machines. The compact model showcases a low pivot boom to allow better cab visibility for the operator while transporting loads. Obviously, the compact telehandler has narrower and tinier dimensions. The reach capacity for compact units is between thirteen to twenty feet and these units offer a lift capacity from five to seven thousand pounds. The versatility of the compact telehandler makes it popular in a variety of applications. Telehandlers can function as a pick and place unit or a tool carrier. Compact units are ideal for cramped locations. Residential applications are common as contractors relish their useful nature with framing applications and where height restrictions come into play. Telehandlers can enter internal building access in hard-to-reach locations. Compact telehandlers are used in many applications including nurseries,

erecting steel, multi-story construction, masonry, strip malls, garages and similar jobs. Telehandlers are employed by agri-business and farming applications to complete many jobs. Telehandlers come with crab steering or two or four-wheel drive options. The unit can travel over longer ranges at higher speeds with two-wheel drive, making it ideal for moving throughout job sites. The 4-WD units are capable of having a tighter turning radius and can travel difficult terrain. Crab steering increases overall maneuvering and enables the front and back wheels to move 45 degrees to the left or the right. Compact telehandlers have varying cab environments. On entry-level models, there is a rollover cage for added safety. Higher models come with a heater, a completely enclosed cab, defroster and windshield wiper. All compact telehandler cabs are spacious to accommodate the operator as comfortable as possible. Extra amenities including air conditioning, satellite radio, suspension seats, tilt steering and cup holders are available. The numerous attachment options are facilitated with high-pressure and high-flow auxiliary hydraulics. The different attachments allow the machine to be capable of many options. All of these attachments enable the machine to conduct a variety of jobs. Compact units are more commonly utilized for ground engaging jobs. It is simple to transform a compact telehandler into a mini excavator with a bucket attachment. Light-duty to heavy-duty buckets can be attached for transferring material, side-shifting and rotating fork carriages are relied on for pick and place situations, augers for drilling post holes or planting trees or pier supports, truss booms for extending reach, crane hooks, brooms for sweeping and more. Skid steer attachments are being manufactured for certain compact telehandler designs for even more versatility.